
1) 1) 11 (a. 1) 15 (b. 1)






FIG. 4

STRUCTURE OF MASTER FILE






FIG. 5



SELECTION OF APPLIED MODEL
LIST OF APPLIED MODELS
BJC-4200 SYSTEM
BJC-420J
BJC-420J (BLACK)
BJC-4300
BJC-430J
BJC-4200LX
A250 II Q
BJC-4200
Old Carrier
OK CANCEL



7/97

FIG. 8

PART NUMBER	PART NAME	QUANTITY	PART NUMBER
PAI	RT .		l
000 - 0000 - 001	PART 001	•	<u> </u>
000 - 0000 - 002	PART 002		
000 - 0000 - 003	PART 003		
001 - 0000 - 001	PART 101		
001 - 0000 - 002	PART 102		
111 - 1111 - 001	PART 001		<b>                                     </b>
A01 - 1234 - 001	TEST PART 0001		

<ul><li>WORK</li></ul>	NAME
------------------------	------

GE \_\_\_

#### CANDIDATES

原稿(GENKO)ガラス保護紙セット(SET ORIGINAL GLASS PROTECTIVE SHEET)

現像(GENZOU)レール戻しバネ掛け(HOOK DEVELOPING RAIL RETURN SPRING)

現像(GENZOU)レール戻しバネ掛け(後)(HOOK DEVELOPING RAIL RETURN SPRING(AFTER))

原稿(GENKOU)台ガラスセット(SET ORIGINAL GLASS TABLE)

原稿(GENKOU)台保護紙セット(SET ORIGINAL TABLE PROTECTIVE SHEET)

現像機(GENZOUKI)トナーなしチェック(CHECK NO TONER IN DEVELOPER)

現像機(GENZOUKI)エラーチェック(CHECK ERROR IN DEVELOPER)

現像機(GENZOUKI)ロック(LOCK DEVELOPER)

• WORK NAME

現像(GENZOU) \_\_\_

• CANDIDATES


現像(GENZOU)レール戻しバネ掛け(HOOK DEVELOPING RAIL RETURN SPRING)

現像(GENZOU)レール戻しバネ掛け(後)(HOOK DEVELOPING RAIL RETURN SPRING(AFTER))


現像機(GENZOUKI)トナーなしチェック(CHECK NO TONER IN DEVELOPER)

現像機(GENZOUKI)エラーチェック(CHECK ERROR IN DEVELOPER)

現像機(GENZOUKI)ロック(LOCK DEVELOPER)



11/97







FIG. 14



00	*	1
01	DO zzzz SUCH THAT xxxx AT wwww POSITION BECOMES yyyy	 
02	WIND AV CORD	
03	CONFIRM 100V SYSTEM	
04	SET CRG HOLDER	

NOTE, STANDARD / REQUIRED QUALITY

NOTE |


SEPARATION GRIPPER MOVES SLOWLY WITHOUT GRIPPER SPRING OF ASFU


DON'T PULL TAPE TOO STRONG TO MAKE SIDE GUIDE LOOSE


DON'T HOOK PAPER GUIDE u ON SHEET HOLDER


BEWARE OF IMITATIONS

BEWARE OF IMITATIONS(Color Style Write










Г			
	WORK STANDARD	SYSTEM	Л
	WORK STANDARD	( <u>F)</u> EDI	T( <u>E</u> ) ILLUSTRATION( <u>I</u> ) SHIPMENT DESTINATION
	CREATE( <u>N</u> ) OPEN( <u>O</u> ) CLOSE( <u>C</u> ) CLOSE ALL	Ctrl + N Ctrl + O	
I	SAVE( <u>S</u> )	Ctrl + S	]
	SAVE REVISE(A)	Ctrl + A	
	SAVE ALL		PART
١	DELETE( <u>D</u> )		
	DELETE FROM LIS	ST	_
	PREVIEW(V)		
	PRINT( <u>P</u> )	Ctrl + P	
	PRINT FROM LIST	<u> </u>	
	END( <u>X</u> )		


	WORK STANDARD	SYSTEM	1
	WORK STANDARD	( <u>F</u> ) EDI	T( <u>E</u> ) ILLUSTRATION( <u>I</u> )
Ì,	CREATE(N)	Ctrl + N	
IL	OPEN( <u>O</u> )	Ctrl + O	
	CLOSE(C)		
ا ا	CLOSE ALL		
	SAVE( <u>S</u> )	Ctrl + S	\
l	SAVE REVISE(A)	Ctrl + A	
	SAVE ALL		
ľ	DELETE( <u>D</u> )		
	DELETE FROM LIS	ST	
ľ	PREVIEW( <u>V</u> )	<u></u>	
	PRINT( <u>P</u> )	Ctrl + P	
<u>ا</u> ۔	PRINT FROM LIST		
	END( <u>X</u> )		
$\prod$			· /
	igspace		•


23/97

FIG. 23


WORK STANDARD SYSI	'STEM				$\boxtimes$
• LATEST REVISION NUMBER	N NUMBER O ALL				
MANAGEMENT NO.	REVISION NUMBER	WORK NAME	DATE OF F	DATE OF REGISTRATION	
SO - 04 - 01(4) - E	01	ASFu取付	,	1997/09/13	•
SO - 01 - 01(3) - E	10	ベース・トレーu取付	•	1997/09/01	
SO-01-03-E	10	ベース・トレーu取付		1997/09/01	_
SO - 01 - 04 - E	10	ベース・トレーu取付		1997/09/01	$\exists$
			1		F
SO - 06 - 01 - E	01	線処理			
SO - 06 - 02 - E	10	線処理	•	1997/09/01	
SO - 06 - 03 - E	10	線処理	•	1997/09/01	
SO - 07 - 01(2) - E	10	レールグリス塗布	•	1997/09/01	
SO-08-01-E	01	フール取付		1997/09/01	•
					1
			ý	CANCEL	
			2301		








26/97



28/97



r	_
WORK STANDARD : TRANSLATION SYSTEM (PROTOTYPE)	<u> </u>
O WOLLY OLINDALD DATA	
O MASTER DATA	
[]	
UPLOAD WORK STANDARD	
DOWN! OAD WORK STANDARD	
DOWNLOAD WORK STANDARD	
TRANSLATE WORK STANDARD	
THANGLATE WORK STANDARD	
END	
LIND	

~3000 × 3004 --DISPLAY LANGUAGE-AUTOMATIC TRANSLATION CHECK CLOSE  $\times \times \times \times$ O JAPANESE ENGLISH TRANSLATE ALL  $\times \times \times$ 3003 O UNTRANSLATED O UNCHECKED 3005 -DISPLAY DATA O ALL TRANSLATE 3001 3002 3008 切換アームAssy組立 伝達ローラu取付 紙押え取付 OTOTAL OUNIT ASSEMBLY 伝達ローラu取付 **WORK NAME** クリーナu取付 クリーナu取付 クリーナu取付 VIEW PREPUCES NAME : | PLATEN UNIT 3007 REPRESENTATIVE MODEL NAME : | A252 REVISION NUMBER CANCEL SELECT TRANSLATION OF WORK STANDARD 2 2 2 2 2 2 5 MANAGEMENT NO. SELECT ALL PT - 090 - 010 PT - 010 - 010 PT - 010 - 030 PT - 080 - 010 PT - 010 - 020 PT - 070 - 030 PT - 100 - 010 3008

30/97


FIG. 30

# .

X 0				31/97					
			Part Name Oty	Oty PN	No.   Precaution / Conditions	02 - 01	dge. 03 - 01 No Table Data 1	Procedure No Table Data 1	Page No. PN-030-020
TRANSLATION OF WORK STANDARD (PROTOTYPE) WORK STANDARD(F) II LISTRATION(I) VOICE(S) WINDOW(W)	WORK STANDARD PN-030-020 01 New crested by (PX2056) A252 PUMP UNIT	Model QG5-1319	Part No. Part Name Oty Part No.	Total	No. Procedure	<del> </del>	03 Check press-fitting the blade lever shaft leading edge to the braid folder leading edge.	Details is of Revision Data By OK  O1 New Created by (PX2056)	


D B D Stor H B B D B W

FIG. 32



32/97

FIG. 33



SOUND-SOUND RECORDER	
$FILE(\underline{F})$ $EDIT(\underline{E})$ $EFFECT(\underline{S})$ $HELP(\underline{H})$	
POSITION 0.00SEC	TIME 60.00SEC

35/97

FIG. 35 **VOICE** VOICE **VOICE** VOICE WORK PROCEDURE DATA WORK PROCEDURE DATA (JAPANESE) (ENGLISH) TRANSLATION SYSTEM WORK STANDARD SYSTEM WORK PROCEDURE DATA WORK PROCEDURE DATA (ENGLISH) (JAPANESE) VOICE VOICE VOICE VOICE





FIG. 37

SET CONDITION	SO	MANHOUR	FREQUENCY	ELEMENT WORK NAME	No.

FIG. 38
STANDARD MATERIAL DATA

	,	 
SET CONDITION DATA		
VERB		
COMMENT 2		
OBJECT		
COMMENT 1		

T11223  $\sim$  3902 STANDARD MATERIAL DATA ASHD T11222 T11221 FIG. 39 T134  $\sim$  3901 STANDARD MATERIAL DATA SPG3 T133 **₹ T132** 



D H U S. H H H H H H H H H

# FIG. 41

3601

EDITING OF ELEMENT WORK

FILE(F) EDIT(E) VIEW(V) ANALYZE(A) ANALYSIS MATERIAL(B) CS(S) END(X)

UNIT WORK NAME: SEPARATION ROLLER ATTACHMENT

No.	ELEMENT WORK NAME	FREQU	JENCY	MANHOUR	CS	SET CONDITION
1	負荷バネを負荷バネ取付治具に組込む (SET LOAD SPRING IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1			
2	治具のSWをONにする (TURN ON SW OF TREATMENT DEVICE)	1	1			
3	分離ローラ軸を負荷バネ取付治具に取込む (SET SEPARATION ROLLER SHAFT IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1			
4	治具のSWをOFFにする (TURN OFF SW OF TREAMENT DEVICE)	1	1			
5	分離ロ-ラ軸を治具より外す (DETACH SEPARATION ROLLER SHAFT FROM TREAMENT DEVICE)	1	1			



### • ELEMENT WORK NAME

No.	COMMENT 1	OBJECT	COMMENT 2	VERB
1		負荷バネを	負荷バネ取付治具に	組込む
2	治具の	SWを		ONする
3		分離ローラ軸を	負荷バネ取付治具に	組込む
4	治具の	SWを		OFFにする
5		分離ローラ軸を	治具より	外す

## FIG. 42

3601

EDITING OF ELEMENT WORK

FILE(F) EDIT(E) VIEW(V) ANALYZE(A) ANALYSIS MATERIAL(B) CS(S) END(X)

UNIT WORK NAME : SEPARATION ROLLER ATTACHMENT

No.	ELEMENT WORK NAME	FREQU	JENCY	MANHOUR	CS	SET CONDITION	
1	負荷バネを負荷バネ取付治具に組込む (SET LOAD SPRING IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1	41	SPG3	T133/M11/0	
2	治具のSWをONにする (TURN ON SW OF TREATMENT DEVICE)	1	1	8			
3	分離ローラ軸を負荷ハ・ネ取付治具に取込む (SET SEPARATION ROLLER SHAFT IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1	37	ASHD	T11222/T1111	
4	治具のSWをOFFにする (TURN OFF SW OF TREAMENT DEVICE)	1	1	8			3
5	分離ロ-ラ軸を治具より外す (DETACH SEPARATION ROLLER SHAFT FROM TREAMENT DEVICE)	1	1	16	PUMB	T2111 / T111111	
					1	1	

MATCH

SEARCH KEYWORD(KW)

			<u> </u>	\	V	
No.	COMMENT 1	OBJECT	COMMENT 2	VERB	MANHOUR STANDARD MATERIAL	TIME VALUE
1	*	*バネを	*(:	組込む	SPG3 T133/M11/0	41RU
2	*	* <b>&amp;</b>	*に	組込む	ASHED T11222/T1111	37RU
3	*	* ē	*より	外す	PUMQ T2111/T111111	16RU
4	*	* Eリング を	*	組込む	RIN2 T11211 / SO	76RU
5	*	* コネクタ を	*	差し込む	CONN T11211/SO	41RU
6	*	*	*	増し締めする	SCR6 M211/1	23RU

# F I G. 43

3601

### EDITING OF ELEMENT WORK

FILE(F) EDIT(E) VIEW(V) ANALYZE(A) ANALYSIS MATERIAL(B) CS(S) END(X)

UNIT WORK NAME: SEPARATION ROLLER ATTACHMENT

No.	ELEMENT WORK NAME	FREQU	JENCY	MANHOUR	CS	SET CONDITION	
1	負荷バネを負荷バネ取付治具に組込む (SET LOAD SPRING IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1	41	SPG3	T133/M11/0	
2	治具のSWをONにする (TURN ON SW OF TREATMENT DEVICE)	1	1	8		/GET:-50E/M:-10E	
3	分離ローラ軸を負荷パネ取付治具に取込む (SET SEPARATION ROLLER SHAFT IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING)	1	1	37	ASHD	T11222 / T1111	
4	治具のSWをOFFにする (TURN OFF SW OF TREAMENT DEVICE)	1	1	8		/GET:-50E/M:-10E	
5	分離ロ-ラ軸を治具より外す (DETACH SEPARATION ROLLER SHAFT FROM TREAMENT DEVICE)	1	1	16	PUMB	T2111 / T111111	
					1	1	


MATCH

			```		V	
No.	COMMENT 1	OBJECT	COMMENT 2	VERB	VERB PATTERN	TIME VALUE
1	治具の	SWを		ONする	/GET:-50E/M:-10E	8RU
2	治具の	SWを		OFFする	/GET:-50E/M:-10E	8RU
3		読取操作部uを		閉める	/GET:-50E/M:-50E	10RU
4		CRGドアを		閉める	/GET:-50E/M:-50E	10RU
. 5		読取操作部uを		閉める	/GET:-50E/M:-50E	10RU
6		電源コート・を		抜く	/GET:-50EGr2/M:-10E	16RU
7		測定用電源コート・を		抜く	/GET:-50EGr2/M:-10E	16RU

3601

/GET:-50E/M:-10E /GET:-50E/M:-10E SET CONDITION T2111/T111111 ASHD | T11222/T1111 T133/M11/0 PUMB SPG3 S FREQUENCY | MANHOUR | 37 9 ω ω END(X) ROLLER SHAFT IN TREATMENT DEVICE FOR ATTACHING CS(S) 分離中ラ軸を治真より外す(DETACH SEPARATION ROLLER 負荷バネを負荷バネ取付治具に組込む(SET LOAD SPRING IN TREATMENT DEVICE FOR ATTACHING LOAD SPRING) DEVICE) 分離ロラ軸を負荷バネ取付治具に取込む(SET SEPARATION LOAD SPRING) 治臭のSWをOFFにする(TURN OFF SW OF TREAMENT 治具のSWをONにする(TURN ON SW OF TREATMENT EDIT(E) VIEW(V) ANALYZE(A) ANALYSIS MATERIAL(B) ELEMENT WORK NAME UNIT WORK NAME: SEPARATION ROLLER ATTACHMENT SHAFT FROM TREAMENT DEVICE EDITING OF ELEMENT WORK DEVICE) FILE(F) ~ 4 က S

FIG. 45









FIG. 47







49/97



3601 MANHOUR SETTING FILE -2801 5002 5003 5001 STANDARD MANHOUR PROCESSING STANDARD MATERIAL CREATION ANALYSIS MATERIAL CREATION STANDARD MANHOUR SETTING SYSTEM 2804 2806 LOAD FROM WORK STANDARD SYSTEM 2800 STANDARD MATERIAL FILE ANALYSIS MATERIAL FILE WORK DATA FILE

FIG. 50






Component SYMBOL : BJ - 4200   NAME : BJ - 4200   PREVIOUS UPDATE DATE		
NAME : BJ - 4200  NAME  XXXX  HECK PROCESS  ACKAGE	EDIT(E)	
MPONENT SYMBOL NAME : BJ - 4200  MAME  XXXXX  CHECK PROCESS  PACKAGE		
MPONENT SYMBOL  XXXXX  CHECK PROCESS  PACKAGE		
CHECK PROCESS PACKAGE		PREVIOUS UPDATE DATE
CHECK PROCESS PACKAGE		1997/09/22 11:09:59
PACKAGE	CHECK PROC	1997/09/12 11:09:59
		1997/09/18 11:21:07
NEXT   DOWNLOAD   UPLOAD   BACK UP   LIST   CANCEL ACCESS FLAG   END	DOWNLOAD UPLOAD BACK UP	CANCEL ACCESS FLAG

			F1G. 54		
SEL	SELECTION OF MODEL				
	FILE(E) EDIT( $\underline{E}$ ) VIEW( $\underline{V}$ )	Prince and the second s			
	PRODUCT NUMBER : BJ-970909 COMPONENT SYMBOL : CH		NAME: 97 - 09 - 09 LOAD NAME:		
	SET MODEL SYMBOL	QUANTITY	NAME	PREVIOUS PUBLICATION DATE	
	A250 IIQ				
	BJC - 4200LX	+             	1 1 1 1 1 1 1 1 1 1 1 1		
	BJC - 4200 SYSTEM	+ 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1	T	
	BJC - 420J	— —               	1 1 1 1 1 1 1 1 1		
	BJC - 420J(BLACK)	               	1 1 1 1 1 1 1 1 1 1 1		
	BJC - 4300		XXXXX		
	BJC - 430J	+ — - 1 1 1 1 1 1 1 1 1		T	
	NEXT REGISTER PU	PUBLICATION	LOOK PUBLICATION	DISPLAY SAME MODEL END	
					$\neg$

FIG. 55

ſ			 				`	5	55/	97						<del>.</del>	 		7
			097 - 09 - 09 LOAD SET MODEL SYMBOL: BJC - 4300 REVISION NUMBER DISPLAY	WOLTHOUGH TO TOU PRINCE THAT YEAR THE	튐	1   電気チェック   0   0   0   1	1   電気チェック   0   0   0   1	1 電気チェック 0 0 0 0 0 1 0 1	1 電気チェック 1 0 1 0 1 0 1 1	1 電気チェック 0 0 0 0 1 1	1 フロントカバーu取付 0 0 0 0 1	1   フロントカバーu取付   0   0   0   1	1 フロントカバーu取付 0 1 0 1 0 1 1	1   フロントカバーu取付 0   0   0   1 ▼	UNIT WORK NAME (MANHOUR USE FREQUENCY 1 2 3 4 5		© CHANGE O INSERT O ADD CHANGE O INSERT O ADD CHANGE		5506 5502 5503 5504 5505
	SELECTION OF MODEL	FILE(E) EDIT( $\underline{E}$ ) VIEW( $\underline{V}$ )	OL : BJ - 970909 NAME : MBOL : ON NAME :	CEACENIT NO	TONIMAL MAINAGEMENT NO.	► N 3 CH-01-01	N; 4 CH-01-02(1)	N; 5 ! CH-01-02(2)	N 6 1 CH-01-03	N' 7 ' CH-01-04	N; 23 (CH-07-02(1)	Ni 24 i CH-07-02(2)	N 25 i CH-07-01(3)	N  26   CH-07-01(4)	No. FORMAL MANAGEMENT NO.	3 CH-01-01			5501 5507


FIG. 56



l G. 57

LYSI	EDITING OF ANALYSIS MATERIAL								
FILE(E) EDIT( <u>E</u> ) VIEW( <u>V</u> )	:W( <u>V</u> )								
PRODUCT GENRE :	: ALL								
TYPE COMMENT 1	OBJECT	COMMENT 2	VERB	ANALYSIS SYMBOL MANHOUR USE FREQUENCY	MANHOUR	USE	REQUENC	Y COUNT	SET DATE
IP-\$477°:	本体を	矢印1の様に	入れる	-50/Gr1/N/>6/-3	15	0	-	0	97/09/09 9:52
17-4477°:	本体を	矢印1の様に	入れる	-50/E/02/N/-6	=	0	-	0	97/09/09 9:53
IP-キャッフ。:	本体を	矢印1の様に	入れる	-50/Gr1/N/>6/-3	15	0	-	0	97/09/09 9:55
	要素作業01		動詞	-50/Gr1/N/>6/-3	15	0	-	0	97/09/10 16:34
17-4477°:	本体を	矢印1の様に	入れる	-50/Gr1/N/>6/-3	15	0	-	0	97/09/10 19:09
	キャリッシ・ロック		2	Time100/Rate100	100	9	-	-	97/09/10 19:16
₹-9-組立る:	プリンタシャーシ		入れ、セルする	M211/1/10	20	-	-	-	
	プリンタシャーシ		裏面にする	T1221/M2311/0/0	12	0	-	0	97/09/11 17:34
	-		1	T2221/M1211/0/1	24	0	-	0	97/09/11 17:20
	2		2	T1221/M2311/0/0	12	0	-	0	97/09/11 17:24
	フ・リンタシャーシ	PRが1が取付る	取付るセ小する	1	15	0	-	0	97/09/12 11:24
	dgdfafdfas		fdasfdasfasfad	*	16	0	-	0	97/09/12 12:10
	dsdsffsfdsdsaf		fdsafdaddfds	T21121/M1111/0/1	13	0	-	0	97/09/12 12:10
	dgdfafdfas		fdasfdasfasfad	*	16	0	-	0	
	フ・リンタシャーシ	PRが作取付る	セットする		15	0	-	0	97/09/12 14:00
	フ・リンタシャーシ	PRガイド取付る	セルする		5	0	-	0	97/09/12 14:00
	7.424.6		もかする	Time100/Rate100	100	8	-	0	97/09/12 14:04

FIG. 58




O 16. DSY CANCEL 12. GET O 11. PU 14. MA O 15. ASY O 13. M FIG. 59 5902 SELECT O 10. BODY 8. UMAC O 6. DSY 9. MP 7. R SIMO () 2. GET O 5. ASY 1. PU 3. M 5901


F1G. 60

60/97


9 വ >50cm က 6003 FORMULA >3Kg +10cm -6mm Qr-2 YES 6002 SET VALUE MANUAL -10mm <3Kg -10cm Q -3 9 CANCEL PICK UP 1 : | MOVING DISTANCE 3 : PRE-POSITIONING 6001 GRIP TYPE MAIN SIZE WEIGHT SET XXXXXX  $\mathbb{S}$ 5: 9

F1G. 61






63/97 1997/09/22 14.30.00 CHANGE DATE (NEW) PREVIOUS (PREVIOUS) (PREVIOUS)
USE MANHOUR MANUAL USE 0 0 END 6302 0 ▶ CE CE FIG. 63 0 6301 UNIT WORK NAME CODE REASON MANHOUR MANUAL SEARCH 9 숭 REASON CODE 1 CHANGE REASON SET 9 O FROM ○ BEFORE O ~ SET П ► CH-01-01: ELECTRICAL CHECK 0 CORRECTION OF CHANGE LOG 22 60 --DATE ---1997 9 S



WINDOW DISPLAY
OUTPUT CONSIDERING
PARALLEL OPERATION 6506 SIMPLE DIVISION WINDOW DISPLAY OUTPUT 6504 6505 **EXCEL OUTPUT** 6503 DIVISION CONDITION OUTPUT 6501 2802 FIG. 65 OPERATOR DATABASE WORK ASSIGNMENT SYSTEM COMPOSITION RANGE INPUT 6502 6400 COMPOSITION TABLE FILE

65/97



F1G. 67

			SIMPLE DIVISION PARALLEL DIVISION
<b>▲   ◆ ▶</b>		<u></u>	
<b>&gt;</b>		MANHOUR	134 550 270 365 268 117
FILE(F) EDIT(E) INPUT(I) TOOL(O)	GP55	WORK NAME	STICK HANDY CUT TAPE SET LABELS ON MAIN BODY WEIMAN REMOVAL ASSEMBLE OUTER CASE FIT TOP PAD STICK LARGE-SIDE ORDER LABEL
— FILE(F) EDIT(E	MODEL	STANDARD NO.	0001 0002 0003 0004 0005

### SIMPLE DIVISION

-			▼	•
FILE(F) EDIT(E)				<b>\$</b>
St 1		_		
0001	STICK HANDY CUT TAPE	134		
0002	SET LABELS ON MAIN BODY	550		
0003	WEIMAN REMOVAL	270		
St 2				1
St 2	ASSEMBLE OUTER CASE	365		
St 2				






FIG. 70





### 7,1/97

## FIG. 71


### PARALLEL DIVISION









F1G. 74





76/97



7710	THE EXPECTED NUMBER OF PRODUCTS. 650] UNITS!  THE NUMBER OF DEFECTIVE PRODUCTS. 656 UNITS!  THE NUMBER OF INITAL PRODUCTS. 656 UNITS!  THE NUMBER OF INITAL PRODUCTS. 656 UNITS!  INVESTED INTO TOP OF ASSEMBLY LINE. 656 UNITS!  MORNING MEETING TIME. 1 UTES!  EXPECTED COMPOSITION EFFICIENCY: 95 % 7710C  COMPOSITION EFFICIENCY 100 % 1720C  COMPOSITION EFFICIENCY 100 % 1720C  THE NUMBER OF STATIONS: 18.51  THE NUMBER OF STATIONS: 18.55  BY PITCH TIME (IP) 660 RU	EXECUTE COMPOSITION   END   7730
77 FIG. 77 7702 7705 7703	O WORK O TOOL OPART ONOTE	1 (UH) 0 (HU) 277 (19) 777


#### 78/97

	INSERTION OF UNIT WORK	×
	NEW WORK WILL BE INSERTED BEFORE "STICK CHECK SHEET SERIAL NO."  INPUT WORK NAME AND PROVISIONAL MANHOUR VALUE	
7801-	UNIT WORK NAME :	
	PROVISIONAL MANHOUR : (RU)	
7802 -	REMARKS :	
	OK CANCEL	

D H H Va. B H B B B W

79/97

FIG. 79



F1 G. 80





FIG. 81




#### STATION 1


WORK NAME	MANHOUR
A1	10
A2	20
А3	12
A4 - 1	25
A4 - 2	25


#### STATION 2

WORK NAME	MANHOUR
B1	10
B2	25
В3	11
B4	8

MANHOUR IN STATION = 92 ~













FIG. 85






87/97

FIG. 87






DIRECTORY NAME IMAGE DATA	IMAGE DATA	OPERATION (VERB)	PARAMETER 1	PARAMETER 2	PARAMETER 3
xxxxxx1	SCREW	SCREW	SCREW CLOCKWISE	SCREW CLOCKWISE DISTANCE MOVEMENT 10mm	TORQUE 10Kg.M
xxxxx2	SCREW	SCREW	SCREW CLOCKWISE	DISTANCE MOVEMENT 20mm	TORQUE 20Kg.M
ххххххЗ	SCREW	SCREW	SCREW CLOCKWISE	DISTANCE MOVEMENT 20mm	TORQUE 30Kg.M
•	:	:			
уууууу1	ROTATE	ROTATE	CLOCKWISE	DISTANCE MOVEMENT 20mm	
уууууу2	ROTATE	ROTATE	COUNTERCLOCKWISE	COUNTERCLOCKWISE DISTANCE MOVEMENT 20mm	
÷	:	:			•
122222	OPEN	OPEN	OPEN UPWARD	DISTANCE MOVEMENT 30mm	WEIGHT 100g
222222	OPEN	OPEN	OPEN DOWNWARD	DISTANCE MOVEMENT 40mm	WEIGHT 200g
• • •	•	•	:		


89/97


90/97


FIG. 90




	9101	9102
SETTING OF COMPONENT SYMBOL		
PRODUCT SYMBOL : BJ - 970909  COMPONENT SYMBOL : CH		
COMPONENT NAME : CHECK		
OK SEARCH COMPONE	ENT	CANCEL







95/97




N ST: THE NUMBER OF STATIONS

n; : i STATION PARALLEL NUMBER

no : TOTAL ACCUMULATED PARALLEL

SUM NUMBER



 $T_A = WF/N_{ST}$ 

SUM NUMBER

To: TOTAL ACCUMULATED MANHOUR

n;: i STATION PARALLEL NUMBER

no: TOTAL ACCUMULATED PARALLEL





97/97

